

# On the Design of the Fiber To The Home Networks

Stefano Gualandi, Federico Malucelli, Domenico L. Sozzi

*Politecnico di Milano, Dipartimento di Elettronica e Informazione  
Piazza Leonardo da Vinci 32, 20133 Milano, Italy  
{gualandi,malucell,sozzi}@elet.polimi.it*

*Key words:* LP-based Randomized Rounding, Local Search, Network Design

---

## 1 Introduction

Telecommunications network design is the source of many interesting challenges in combinatorial optimization. Among the more recent ones there is the design of the Next Generation Access Networks completely based on fiber cable technology that, in certain cases, may reach single users and for this reason are called Fiber To The Home networks (FTTH). These networks are organized into two levels. In the first level few *central offices* are connected with high capacity fiber cables to *splicing cabinets* usually located at street intersections. Cabinets are then connected with users or houses. The fiber technology allows to have very long connection cables thus few central offices suffice to serve many more users with respect to traditional copper based networks. The new network characteristics and the incumbent deployment, that requires a great extent of investments, motivate the investigations on quantitative optimization models and algorithms for the planning that can help investors to decide which type of fiber network to select and how to operationally implement it. For a review on technical aspects refer to [2].

## 2 Problem Statement and Formulation

Planning a FTTH network can be seen as a particular case of facility location problem where facilities belong to two levels. Given a set of candidate sites  $O$  for central offices, a set of candidate sites  $C$  for cabinets and the set of homes to be served  $S$ , the problem consists in deciding in which candidates sites install central offices and cabinets, and connect users to central offices

passing through a cabinet. In addition to these decisions the problem considers also the multiplexing capability of cabinets. Depending on the type of device installed in the cabinet, several signals transmitted on fibers to the users can be groomed into a single fiber to the central office thus allowing for a capacity saving in the leg central office-cabinet. The additional decision level is thus the type of multiplexing technology to be installed in each cabinet. Decisions must consider central office and cabinet installation costs, multiplexing technology costs, and cable deployment costs.

Let  $s_i^1$  and  $M_i^1$  be the cost and the capacity (in terms of number of fibers) of central office  $i$ . Let  $T$  be the types of technologies that can be installed in cabinets. Multiplexing technology  $t$  in a cabinet allows to send  $m_t$  channels on a single fiber towards the central office. Let  $s_{jt}^2$  be the installation cost of cabinet  $j$  with technology  $t$ , and  $M_j^2$  its maximum capacity in terms of number of fibers coming from the users. With  $d_{ij}$  we indicate the known distance (computed on the street graph) between any two sites  $i$  and  $j$ .

A possible formulation of the problem introduces two sets of binary variables:  $y_i^1, i \in O$  whose value is 1 if a central office is activated in site  $i$ , and  $y_{jt}^2, j \in C, t \in T$  if a cabinet with multiplexing technology  $t$  is activated in site  $j$ . We need another set of binary variables  $x_{jl}^2$  whose value is 1 if basement  $l$  is assigned to cabinet  $j$ . Integer variables  $x_{ij}^1$  give the number of fibers connecting central office  $i$  with cabinet  $j$ . The last two sets of variables are defined for all pairs  $i, j$  and  $j, l$  such that the distance between the corresponding sites is less than or equal to the maximum allowed distance. In order to consider only pairs of sites within a feasible distance, we introduce a set  $E$  of pairs  $i, j$  with  $i \in O$  and  $j \in C$  such that  $d_{ij} \leq L^1$ , and a set  $F$  of pairs  $j, l$  with  $j \in C$  and  $l \in S$  such that  $d_{jl} \leq L^2$ .

The Integer Programming model is as follows:

$$\min \quad \sum_{i \in O} s_i^1 y_i^1 + \sum_{j \in C} \sum_{t \in T} s_{jt}^2 y_{jt}^2 + \sum_{ij \in E} c_{ij}^1 x_{ij}^1 + \sum_{jl \in F} c_{jl}^2 x_{jl}^2 \quad (1)$$

$$\text{s.t.} \quad \sum_{jl \in E} x_{jl}^2 = 1, \quad \forall l \in S, \quad (2)$$

$$\sum_{ij \in E} x_{ij}^1 \leq M_i^1 y_i^1, \quad \forall i \in O, \quad (3)$$

$$\sum_{t \in T} y_{jt}^2 \leq 1, \quad \forall j \in C, \quad (4)$$

$$\sum_{jl \in F} x_{jl}^2 \leq M_j^2 \sum_{t \in T} y_{jt}^2, \quad \forall j \in C, \quad (5)$$

$$m_t \sum_{ij \in E} x_{ij}^1 \geq \sum_{jl \in F} x_{jl}^2 - M_j^2 (1 - y_{jt}^2), \quad \forall j \in C, \forall t \in T, \quad (6)$$

$$y_i^1 \in \{0, 1\}, \forall i \in O, \quad y_{jt}^2 \in \{0, 1\}, \forall j \in C, \forall t \in T, \quad (7)$$

$$x_{ij}^1 \in \mathbb{Z}_+, \forall ij \in E, \quad x_{jl}^2 \in \{0, 1\}, \forall jl \in F. \quad (8)$$

Constraints (2) state that each user must be connected to a cabinet. Constraints (3) are twofold: they force the activation of central office  $i$  (i.e. it sets variable  $y_i$  to 1) if at least one cabinet  $j$  is assigned to it, and they limit the number of cabinets assigned to  $i$  according to the capacity. Constraints (4) determine that either a cabinet is not active (when the left hand side is equal to 0) or at most a multiplexing technology is assigned to it. While constraints (6) relate the number of incoming fibers in a cabinet from users with the number of outgoing fibers towards the central office. This number must account for the multiplexing factor installed in the cabinet. The objective function (1) sums up the cost  $s_i^1$  of each selected central office, the cost  $s_{jt}^2$  for installing the technology  $t$  in cabinet  $j$  and the connection costs for the fibers between central offices and cabinets and between cabinets and the users.

In order to improve the linear relaxation, we introduce the following constraint:

$$\sum_{t \in T} y_{jt}^2 \leq \sum_{ij \in E} x_{ij}^1, \forall j \in C. \quad (9)$$

that states that if a cabinet is activated it must be connected to a central office. Though the improvement on the lower bound is modest, this constraint does have an impact on our LP-based randomized rounding algorithm.

### 3 Solution Approaches and Computational Results

We have developed two approaches to solve the FTTH problem. The first approach is a LP-based Randomized Rounding (LP-RR) algorithm, the second is a Constraint-Based Local Search (CBLS) algorithm. Both approaches are implemented exploiting features of the COMET constraint language [3]. For the lack of space, we just briefly sketch the two approaches.

Our LP-RR algorithm, motivated by the results in [1], is based on the observation that once we have decided which central offices and which cabinets are opened, that is, the variables  $y^1$  and  $y^2$  have been fixed to either 1 or 0, the remaining problem is reduced to a generalized minimum cost flow problem on a tripartite graph. So we first randomly round the variables  $y^1$  and  $y^2$ , and only then, the  $x^1$  and  $x^2$  variables.

The proposed CBLS approach relies on the use of *invariants* (see [4]) to incrementally maintain the necessary information to guide the search procedure. Once a greedy procedure has computed a feasible solution, we execute a local search algorithm based on a simple move: select the basement  $l$  connected to a cabinet  $j$ , and select a different open cabinet  $j' \neq j$  that is not saturated (it has some capacity left) such that *moving*  $l$  from  $j$  to  $j'$  gives, after the propagation of the new assignments, the best improvement in the objective

Table 1

LP-based Randomized Rounding (LP-RR) versus Constraint-based Local Search (CBLS). Cost and Time (in seconds). Standard deviations omitted.

			LP-RR			CBLS		
$ O $	$ C $	$ S $	Cost	Time	Best-Cost	Cost	Time	Best-Cost
3	10	100	2383	31	<b>2383</b>	<b>2383</b>	0.6	<b>2383</b>
10	35	400	6979	716	6966	6864	1.2	<b>6860</b>
15	65	841	13630	1735	13599	13349	44.6	<b>13306</b>
20	100	1521	25499	2465	25427	24850	316	<b>24752</b>
25	120	3025	55073	4768	55052	51752	330	<b>51646</b>
30	140	6084	121794	7705	121974	118224	1105	<b>118135</b>
35	150	10000	239668	26915	239668	229677	1817	<b>229244</b>

Table 2

Solving big Rome instances with the CBLS approach: gaps computed with respect to the linear relaxation (P).

$ O $	$ C $	$ S $	Cost (stdev)	Time (stdev)	Best-Cost	LP-Gap
30	140	5982	4561215 (0.01%)	1803.6 (0.14%)	4560780	0.9%
30	140	5995	4164941 (0.01%)	2168.7 (0.69%)	4164724	1.1%
30	140	6014	3462920 (0.01%)	1426.9 (0.35%)	3462857	1.4%
35	150	10020	3126763 (0.02%)	2511.8 (0.44%)	3126385	2.4%
35	150	10040	5937585 (0.01%)	3484.7 (0.55%)	5936733	1.1%
35	150	10072	6663950 (0.01%)	1183.6 (0.54%)	6663481	0.9%

function. After this move, we possibly increase the number of fibers outgoing cabinet  $j'$ .

Tables 1 shows a comparison of the two approaches, reporting computational results averaged over 5 runs for each problem instance. Even if both approaches are interesting, the CBLS outperforms the LP-RR both in quality and computation time. Table 2 reports the results for a set of realistic instances based on the street graph of the city of Rome. Note that CBLS computes near-optimal solution in short time.

## References

- [1] Barahona, F., Chudak, F.: Near-optimal solutions to large-scale facility location problems. *Discrete Optimization* **2**(1) (2005) 35–50
- [2] Kramer, G., Pesavento, G.: Ethernet Passive Optical Network (EPON): building a next-generation optical access network. *IEEE Communications Magazine* **40**(2) (2002) 66–73
- [3] Van Hentenryck, P., Michel, L.: Control abstractions for local search. *Constraints* **10**(2) (2005) 137–157
- [4] Van Hentenryck, P., Michel, L.: Differentiable invariants. In: Frédéric Benhamou (Ed.), *Proc CP-06 LNCS-4204*. Springer, (2006) 604–619